



Cooling units

TDM7.16 Ref:60TDTDM716PA-01



- ❖ Chiller control machine with static evaporator
- ❖ 1 operating mode
- ❖ Programmable defrost cycles for column
- ❖ Temperature probe NTC 6K8/10K (25C)
- ❖ Temperature range from -40 to 99C
- ❖ Acting on compressor to ICV

TDGH-25 Ref:60TDTDGH25-01



- ❖ Chiller control machine with static evaporator
- ❖ 1 operating mode
- ❖ Control percentage of glycol
- ❖ Temperature probe NTC 6K8/10K (25C)
- ❖ Temperature range from -40 to 99C
- ❖ Conductivity prove SH AISI-304
- ❖ Conductivity range 100µS a 2500µS
- ❖ Acting on compressor to ICV

TDGH-B3 Ref:TDTDGHB3-02



- ❖ Control machine double-Pan V75 & V175 3* Gen
- ❖ 5 operating mode
- ❖ Control percentage of glycol
- ❖ Temperature probe NTC 6K8/10K (25C)
- ❖ Effective temperature range from -40 to 99C
- ❖ Conductivity prove SH AISI-304
- ❖ Conductivity range 100µS to 2500µS
- ❖ Available key use COPYKEY
- ❖ Acting on compressor to ICV

TDORION Ref:60TDTDORION-00



- ❖ Chiller control machine for ORION System.
- ❖ 1 operating mode
- ❖ Temperature probe NTC 6K8/10K (25C)
- ❖ Effective temperature range -40 to 99C
- ❖ Conductivity prove SH AISI-304
- ❖ Conductivity range 100µS to 2500µS
- ❖ Acting on compressor to ICV


TD2T Ref:60TDTD2T-00



- ❖ Chiller control machine for double turbine
- ❖ 1 operating mode
- ❖ Separate drive for turbine control
- ❖ Temperature probe NTC 6K8/10K (25C)
- ❖ Temperature range from -40 to 99C
- ❖ Acting on resistive Loads 16A

Units for cooling and heating

TDFC201R Ref:60TDTDFC201R-01



- ❖ Chiller control machine with static evaporator
- ❖ Heating control system
- ❖ 2 operating mode
- ❖ Programmable defrost cycles for column
- ❖ Temperature prove NTC 6K8/10K (25C)
- ❖ Temperature range from -40 to 99C
- ❖ Acting on compressor to ICV

TDFC202R Ref:60TDTDFC202R-00



- ❖ Chiller control machine with static evaporator
- ❖ Heating control system
- ❖ 2 operating mode
- ❖ Programmable defrost cycles for column
- ❖ Temperature prove NTC 6K8/10K (25C)
- ❖ Temperature range from -40 to 99C
- ❖ Acting on compressor to ICV
- ❖ Acting on external alarm max 6A

ADDITIONAL INFORMATION

The models presented are for connection to 230VAC, but there are similar models connection to 115VAC with references:

- TDM7.16 → Ref: 60TDTDM716PAE-00
- TDGH25 → Ref: 60TDTDGH25E-01
- TDGHB3 → Ref: 60TDTDGHB3E-02
- TDORION → Ref: 60TDTDORIONE-00
- TD2T → Ref: 60TDTD2TE-00
- TDFC201R → Ref: 60TDTDFC201RE-00
- TDFC202R → Ref: 60TDTDFC202RE-00

Our R&D has the ability to design and develop a device to your needs

Now you do not need to fit your device. Our device will suit you!

Thermostats all-in-one 1 Relay

TDAIO1R-00

Ref:60TDAIO1R-00



- Control of cooler /healer machine
- Compact size version
- Multipurpose ways of function
- Multiple connection for NTC probe, conductivity...
- Temperature range from -40 to 99 C
- Conductivity range 100 μ S to 2500 μ S
- Connection with peripheral, copykey, external display...
- Acting on compressor to 1CV / 16 A

TDAIO1R-01

Ref:60TDAIO1R-01



- Control of cooler /healer machine
- Standart size version
- Multipurpose ways of function
- Multiple connection for NTC probe, conductivity ...
- Temperature range from -40 to 99C
- Conductivity range 100 μ S to 2500 μ S
- Connection with peripheral, copykey, external display ...
- Acting on compressor to 1CV/16A

TDAIO1R-02

Ref:60TDAIO1R-02



- Control of cooler /healer machine
- Standart size version
- Multipurpose ways of function
- Multiple connection for NTC probe, conductivity ...
- Temperature range from -40 to 99C
- Conductivity range 100 μ S to 2500 μ S
- Connection with peripheral, copykey, external display ...
- Acting on compressor to 1CV/16A
- Direct connection from compressor to thermostat

Thermostat all-in-one 2 Relays

TDAIO2R-00

Ref:60TDAIO2R-00



- Control of cooler /healer machine
- Compact size version
- Multipurpose ways of function
- Multiple connection for NTC probe, conductivity...
- Temperature range from -40 to 99 C
- Conductivity range 100 μ S to 2500 μ S
- Connection with peripheral, copykey, external display...
- Acting on compressor to 1CV/16A
- Acting on another element until 6A

ADDITIONAL INFORMATION

The models presented are for connection to 230VAC, but there are similar models connection to 115VAC with references:

- TDAIO1R-00 → Ref: 60TDAIO1RE-00
- TDAIO1R-01 → Ref: 60TDAIO1RE-01
- TDAIO1R-02 → Ref: 60TDAIO1RE-02
- TDAIO2R-00 → Ref: 60TDAIO2RE-00

Our R&D has the ability to design and develop a device to your needs

Now you do not need to fit your device. Our device will suit you!